



LED Driver TRIAC 36W 24V - TD-36-24-E1P1

28411

Datasheet

Technical Specs

General	
Product Type	Constant Voltage Driver
Length (mm)	175
Width (mm)	44
Height (mm)	30
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	165
Electronics	
Input Domain	AC
Input Voltage	200 ~ 240V AC
Output Voltage	24V DC
Output Current Max. (A)	1.5
Output Power Range (W)	0~36
Power Supply	Internal
LED Outputs	1
Input Frequency	50Hz, 60Hz
Inrush Current	20A @ 230VAC
Lighting	
Color Range	Single Color
Control	
Output Signal	PWM-CV
Control	TRIAC
Push Dim	yes
Dimming Range	0~100%
Dimming Curve	Linear
Driver Configuration	Software
Number of Channels	1
Wiring	
Wire Strip Length	5mm
Wire Type	2.5mm ²
Protection	
Reverse Polarity	Yes
Protection Class	II
Environmental	
Operating Temperature	-30 ~ 55 °C
Ingress Protection	IP20
Environment	Indoor

2014/30/EU Electromagnetic C EN55015, EN55024:2010,
EN61000-3-2 Class C,
EN61000-3-3, EN61000-4-2;3;4;5;6;8;11,
EN61347-1, EN61347-2-13,
EN 61547:2009, IEC62386

-

ETIM Classification	EC002710 LED Driver
HS Code	8504318050
Country of Origin	People's Republic of China

Regulations

Approvals

CE	√
----	---



Order information

Code	Description
28411	LED Driver TRIAC 36W 24V - TD-36-24-E1P1

