



LED Driver TRIAC 150W 24V - TD-150-24-E1M1

28409

Datasheet

## Technical Specs

### General

Product Type	Constant Voltage Driver
Length (mm)	273
Width (mm)	57
Height (mm)	37
Housing Color	White
Housing Material	Metal
Mounting	Surface mounted
Weight (g)	790

### Electronics

Input Domain	AC
Input Voltage	200 ~ 240V AC
Output Voltage	24V DC
Output Current Max. (A)	6.25
Output Power Range (W)	0~150
Power Factor at Full Load	+0.95 @ 230VAC
Power Supply	Internal
LED Outputs	1
Input Frequency	60Hz
Inrush Current	60A @ 230VAC

### Lighting

Color Range	Single Color
-------------	--------------

### Control

Output Signal	PWM-CV
Control	TRIAC
Dimming Range	0~100%
Dimming Curve	Linear
Driver Configuration	Software
Number of Channels	1

### Wiring

Wire Strip Length	5mm
Wire Type	2.5mm <sup>2</sup>

### Protection

Reverse Polarity	Yes
------------------	-----

### Environmental

Operating Temperature	-30 ~ 60 °C
Ingress Protection	IP20
Environment	Indoor

### EU Declaration of Conformity

2014/30/EU Electromagnetic C IEC62386

-

ETIM Classification	EC002710 LED Driver
HS Code	8504318050
Country of Origin	People's Republic of China

## Regulations

### Approvals

CE ✓



## Order information

Code	Description
28409	LED Driver TRIAC 150W 24V - TD-150-24-E1M1

