

LTECH



Driver DALI 100-400mA 12W - SE-12-100-400- 28219 Datasheet

www.ltech-led.eu | ©2020 | Ltech Europe | All Rights Reserved.

Technical Specs

General

Product Type	Constant Current Driver
Length (mm)	135
Width (mm)	30
Height (mm)	20
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	85

Electronics

Input Domain	AC
Input Voltage	100 ~ 240V AC
Output Voltage	10 ~ 42V DC
LED Output Current (max per o	100~400
Output Power Range (W)	1~12
Power Factor at Full Load	+0.85 @ 230VAC
Power Supply	Internal
LED Outputs	1
Input Frequency	50 ~ 60Hz
Inrush Current	5A @ 230VAC

Lighting

Color Range	Single Color
-------------	--------------

Control

Output Signal	PWM-CC
Control	DALI
Dimming Range	0~100%
Number of Channels	1

Environmental

Storage Temperature	-40 ~ 80 °C
Operating Temperature	-30 ~ 50 °C
Ingress Protection	IP20
Environment	Indoor

EU Declaration of Conformity

2014/30/EU Electromagnetic C EN55015, EN61547, EN61000-3-2
 Class C, EN61000-3-3,
 EN61000-4-2;3;4;5;6;8;11,
 EN61347-1, EN61347-2-13

ETIM Classification	EC002710 LED Driver
---------------------	---------------------

Country of Origin People's Republic of China

Regulations

Approvals

CE ✓



Order information

Code	Description
28219	LED Driver DALI 100-400mA 12W - SE-12-100-400-W1D

