



### General

Product Type	Constant Voltage Driver
Length (mm)	175
Width (mm)	42
Height (mm)	33
Housing Color	Matte Black
Housing Material	Metal
Mounting	Surface mounted
Weight (g)	310

### Electronics

Input Domain	DC
Input Voltage	5 ~ 24V DC
Output Voltage	5 ~ 24 V DC
LED Output Current (max per output)	6000
Output Current Max. (A)	18
Output Power (W)	90W @ 5V, 216W @ 12V, 432W @ 24V
Power Supply	N/A
LED Outputs	3

### Lighting

Color Range	RGB
-------------	-----

### Control

Output Signal	PWM-CV
Control	DMX
RDM Support	Yes
Dimming Range	0~100%
Dimming Curve	Linear
Driver Configuration	Dip Switches
Number of Channels	3

### Wiring

Wire Strip Length	5mm
Wire Type	2.5mm <sup>2</sup>
DMX Socket	Screw Terminal

### Protection

Reverse Polarity	Yes
LED Output Short	Yes
Overload	Yes
Restart after Protection	Yes

### Environmental

Operating Temperature	-30 ~ +65 °C
Ingress Protection	IP20

CE FC IP20 5 year warranty

### Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.