



### Electronics

Input Voltage	100 ~ 240V AC
Output Voltage	12V DC
Output Current Max. (A)	3
Power Consumption (W)	36
Output Power (W)	36W @ 12V
Power Supply	Internal
LED Outputs	1
Input Frequency	50Hz, 60Hz
Inrush Current	40A @ 230VAC

### Lighting

Color Range	Single Color
-------------	--------------

### Control

Output Signal	PWM-CV
Control	DMX
Dimming Range	0~100%
Dimming Curve	Linear
Driver Configuration	Dip Switches
Number of Channels	1
Functions	Push DIM

### Wiring

Wire Strip Length	5mm
Wire Type	2.5mm <sup>2</sup>
DMX Socket	Green Terminal

### Protection

Reverse Polarity	Yes
LED Output Short	Yes
Overload	Yes
Restart after Protection	Yes

### Environmental

Operating Temperature	-30 ~ +55 °C
Ingress Protection	IP20

**CE IP20** 2<sup>year</sup> warranty

### Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.