



### General

Product Type	Constant Voltage Driver
Length (mm)	175
Width (mm)	44
Height (mm)	30
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	165

### Electronics

Input Domain	AC
Input Voltage	100 ~ 240V AC
Output Voltage	12V DC
Output Current Max. (A)	3
Output Power Range (W)	0~36
Power Supply	Internal
LED Outputs	1
Input Frequency	60Hz
Inrush Current	20A @ 230VAC

### Lighting

Color Range	Single Color
-------------	--------------

### Control

Output Signal	PWM-CV
Control	TRIAC
Dimming Range	0~100%
Dimming Curve	Linear
Driver Configuration	Software
Number of Channels	1

### Wiring

Wire Strip Length	5mm
Wire Type	2.5mm <sup>2</sup>

### Protection

Reverse Polarity	Yes
Overload	Yes
Restart after Protection	Yes
Protection Class	II

### Environmental

Operating Temperature	-30 ~ +55 °C
Ingress Protection	IP44

**CE** IP44 **2** year warranty

### Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.