



### General

Product Type	Constant Current Driver
Length (mm)	135
Width (mm)	30
Height (mm)	20
Housing Color	White
Housing Material	Plastic
Mounting	Surface mounted
Weight (g)	85

### Electronics

Input Domain	AC
Input Voltage	100 ~ 240V AC
Input Current max (A)	0.1A @ 230V AC
Output Voltage	2 ~ 12V DC
Output Current (mA) max/output	350~700
Output Power Range (W)	0.7~8.4
Power Factor at Full Load	+0,80 @ 230VAC
Power Supply	Internal
LED Outputs	1
Anti Surge	L-N: 1kV
Efficiency	75%
Leakage current max. (mA)	0.5
Standby Power Loss Max. (W)	0.5
Input Frequency	50 ~ 60Hz
Inrush Current	5A @ 230VAC

### Lighting

Color Range	Single Color
-------------	--------------

### Control

Output Signal	PWM-CC
Control	DALI
Dimming Range	0~100%
Number of Channels	1

### Protection

Protection Class	II
------------------	----

### Environmental

Storage Temperature	-40 ~ +80 °C
Operating Temperature	-30 ~ +50 °C
Ingress Protection	IP20

**CE IP20**

#### Disclaimer

Due to the technical evolution and improvement of our products, the data provided in this document may be updated on a regular basis, and as such, confirmation of this information is strongly recommended prior to the order process. InventDesign is not responsible for any discrepancies in this document following changes in our products. We reserve the right to make changes to our products and to change information, at its sole discretion, without notice.